

# EUROBOARD

## READY MIX JOINT COMPOUND



### **Euroboard Ready Mix Joint Compound**

Perfect finishing come from perfect joint compound materials. It's special vinyl formulation provide smooth, seamless finish for gypsum board wall and ceiling joint. But, which do product fit for this duty ?

Euroboard Ready Mix Joint Compound is the only one answer. Used as final touch up coats in interior gypsum board application, it is an ideal material for embedding fastener, corner surfaces, and also for cracks repairing on gypsum board and brick wall plastering surfaces.





## Packing, Coverage, & Storage

**Pail / Bucket** : 28 kg / 5 kg

**Carton Box** : 20 kg

**For Joint Finishing** : 28 kg, covers approximately 55.48 m<sup>2</sup>

**For Texturing** : 28 kg, covers approximately 20.58 m<sup>2</sup>

Building solutions due to special paper that has resistance to temperature and weather changes.

## Preparation



Store Euroboard Ready Mix Joint Compound at room temperature for 24 hours prior to the application.



Stir content lightly, do not add water.



Use directly from the container when use for covering embedded fasteners, corner beads and trims.



If necessary add ½ pints (250 ml) of water, remix gently.



Do not add in any other material.



Keep container covered when not in use.

### Caution

Sanding dust (from out standing) may cause eye, nose, throat or upper respiratory irritation, long term breathing of large amounts of mica may cause lung disease. Use wet sanding technique to avoid creating dust if dry sanded, wear a NIOSH approved dust mask. Do not take internally. The use of safety glasses is recommended. Keep out of children's reach.

Note : The company reserve the rights to revise any data without prior notice.

Terms and condition apply

## Sanding

Sanding is not allowed. if required, use very fine sandpaper of grit 160.

## Application

1. Apply Euroboard Ready Mix Joint Compound only on dry surface.
2. Apply thoroughly and allow each coat to dry before apply the next.
3. Keep air to the minimum, joint compound surface temperature 26/30°C within working area until joint are completely dry.

## Joint Panel

1. Apply the thin layer of Ready Mix Joint Compound between the Gypsum Board joint with 6" wide blade knife press joint tape firmly into The Ready Mix Joint Compound and embed with 8" wide blade knife.
2. Sufficient Ready Mix Joint Compound must be remain under the Ready Mix Joint Compound over the embedding coat and feather out beyond the first coat.
3. Allow the second coat to dry thoroughly prior to the application of the application of the finish coat.
4. Apply the final finish thin smooth coat to the joints and fasteners and let dry (Use 10" wide blade knife for joints and 6" wide blade for fasteners).

## Application Area

- ☒ Area surface must be clean, dry, free from dust and not glossy before any decorating.
- ☒ Decoration shall be such as painting or texturing
- ☒ All directions by decorating shall strictly adhere according to the conditions as stipulated by decorating materials.



SCAN & EMAIL ME