



Tandus was the pioneer in modular carpets in the US. Today, under the Tarkett banner, it is renowned for its innovative range of carpet tiles, award winning design options and commitment to sustainability.

The Tandus carpet tile range features 100% solution dyed nylon pile with a variety of backings to provide the best combination of aesthetics, performance and sustainability for your project.

## SCALE SERIES LIGHT UP

Scale Series depicts the color and movement of light trails in the city, presenting fascinating patterns composed of continuous, colorful, varying width light bands.



**88001  
LENS**



**88007  
HAZEL**



**88009  
FORMULA**



**88010  
CIVIC**

| Face Construction   | Metric                     | Imperial                    | Procedure  |
|---------------------|----------------------------|-----------------------------|------------|
| Construction        | Level Loop                 |                             |            |
| Gauge               | 50.4 rows/10 cm            | 1/13                        |            |
| Stitches per Length | 41.0 stitches/10 cm        | 10.4 stitches/inch          | ASTM D-418 |
| Tuft Density        | 20.7 tufts/cm <sup>2</sup> | 133.3 tufts/in <sup>2</sup> |            |
| Pile Height Average | 3.0 mm                     | 0.118 inch                  | ASTM D-418 |
| Density Factor      | 197.5 kg/m <sup>3</sup>    | 5,339 oz/yd <sup>3</sup>    | UM44D      |
| Fibre System        | Dynex® Nylon               |                             |            |
| Dye Method          | Solution Dyed              |                             |            |
| Soil Resistance     | Ensure                     |                             |            |

### Backing System

|                           |   |                               |
|---------------------------|---|-------------------------------|
| Product Size              | 666.67 mm x 666.67 mm   | 26.25" x 26.25"               |
| Primary Tufting Substrate | Synthetic Non-Woven   |                               |
| Fusion Coat               | Sealant Vinyl   |                               |
| Backing                   | ECOBOND™ Recycled Content Backing<br>TANDUS ECOPLY™ Backing                               |                               |
| Recycled Content          | Contains approx. 32% overall recycled content including a min. 30% post-consumer content. |                               |
| Minimum Backing Density   | 1,041 kg/m <sup>3</sup>   | 65 lbs/ft <sup>3</sup>        |
| Total Product Weight      | 3,556 g/m <sup>2</sup> ± 5%   | 104.9 oz/yd <sup>2</sup> ± 5% |

### Product Testing Information

|                          |  |             |
|--------------------------|--|-------------|
| Surface Flammability     | Passes CPSC FF 1-70  | ASTM D-2859 |
| Flooring Radiant Panel   | Class I (Mean average CRF: 0.45 watts/cm <sup>2</sup> or higher)   | ASTM E-648  |
| Electrostatic Propensity | 3.0 kV or lower Permanent Conductive Fiber   | AATCC 134   |
| Colourfastness to Light  | ≥ 4 after 100 hours  | AATCC 16E   |
| Fluorine                 | Minimum 500 ppm - Minimum 400 ppm after two hot water extractions  | CRI TM-102  |
| Indoor Air Quality       | All Tandus Flooring products comply with CRI Green Label Plus Standards<br>ID: #GLP5288.<br>Passes GB 18587-2201 |             |



### Warranties

15 year non - prorated limited warranty against excessive surface wear and static, delamination, edge ravel, zippering and backing resiliency loss. See warranty for details.

### Product Notes

- Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature, humidity and colour. Product specifications may vary within normal industry and standardised testing tolerances.
- These specifications reflect mean averages based upon tests of production runs of this carpet style by independent laboratories. A range of variances is implicit in the testing process. Furthermore, the standard test methods established to derive the specifications lack a degree of precision and repeatability; therefore, individual test results on the actual carpet purchased may differ from the specifications above.
- Colours may vary slightly from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements become available which provide for improvement of the product's performance.
- All Tandus Flooring products are 100% recyclable.

\*Custom-made and other designs available upon request. Minimum of 45 days lead time for custom-made and other designs.



SCAN & EMAIL ME

#### MAIN OFFICE

20 Fortune Avenue, corner Santan Street  
Brgy. Fortune, Marikina City, PH 1809  
Phone: +63 (2) 8790-1000  
Fax Sales: (632) 87901015 to 16  
Fax Operations: (632) 87901013 to 14  
Email: info@worldhomedepot.com

#### DAVAO OFFICE

Unit 01-02 DEPC Warehouse, Brgy.  
Communal Diversion Rd., Davao City, PH 8000  
Phone: +63 (82) 234-0911 to 14  
Fax: (082) 2340914  
Email: info.davao@worldhomedepot.com