



CENIT

PUR coated homogeneous sheet & tile / Manufactured in Europe



- The protective polyurethane finish reduces initial and ongoing maintenance and scratch resistance.
- Excellent durability.
- Good stain resistance.
- Very good resilience and resistance to indentation and rolling loads.
- Heat welding blocks dirt and moisture penetration for cleaner looking, more aseptic seams.
- Flexible for easy installation.
- 14 neutral to accent colors and color-coordinated weld rods for design flexibility.
- Applications: education, healthcare, hotels, retails and office interiors.



TECHNICAL INFORMATION

Requirement	Type of floor covering Plastics basis Pattern Flammability Slip resistance Dynamic coefficient of friction Impact sound reduction Decontamination	EN 649 EN 13501-1 BGR 181 EN 13893 ISO 140-8 ISO 8690	Homogeneous with PUR coating Polyvinylchloride Moire B _{fl} – s1 R9 DS 3 dB Good
General Properties	Sheet width Sheet length Tiles: side length Amount of tiles Overall thickness Total weight Residual indentation Color fastness Wear group Electrical insulation to ground Static electrical charge Thermal resistance Thermal conductivity	EN 426 EN 426 EN 427 EN 428 EN 430 EN 433 ISO 105-B02 EN 649 VDE 0100 EN 1815 EN 12667 EN 12524	183 cm 16-25 m 60.8 cm x 60.8 cm 5.54 m ² /pkg 2.0 mm 3,100 g/m ² 0.04 mm ≥ 6 P 200 kOhm ≤ 2.0 kV 0.01 m ² K/W 0.25 W/mK
Classification	Commercial Industrial	EN 685 EN 685	34 very heavy 43 heavy



411-012
● Coral Red
Weld X0545



411-073
● Sunset Orange
Weld X0557



411-071
Amber
Weld X0916



411-063
Salmon
Weld X0908



411-072
● Camel Beige
Weld X0556



411-030
Laguna Green
Weld X0568



411-020
Crystal Blue
Weld X0566



411-062
Pale Khaki
Weld X0563



411-047
● Almond Beige
Weld X0554



411-064
● Coffee Brown
Weld X0555



411-052
Smoky White
Weld X0575



411-051
Grey
Weld X0915



411-050
Hippo Grey
Weld X0573



411-083
● Night Black
Weld X0902



SCAN & EMAIL ME

● NEW COLOR